

RAVENOL CVTF NS2/J1 Fluid

Art. 1211114

ATF Professional Line

Description:

RAVENOL CVTF NS2/J1 Fluid is a fully synthetic CVTF (Continuously Variable Transmission Fluid) produced on the basis of PAO with special additives and inhibition which guarantees a perfect function of the CVT transmission.

RAVENOL CVTF NS2/J1 Fluid is a CVTF of the latest generation. It is especially developed for the CVT transmission of JATCO. It guarantees in any mode for maximum wear protection.

RAVENOL CVTF NS2/J1 Fluid is green coloured.

Application Directions:

RAVENOL CVTF NS2/J1 Fluid is suitable for use in CVT transmission of following vehicles with CVT-transmission:

Peugeot 4007, Citroen C-Crosser, Mitsubishi Outlander, Mitsubishi Delica D5, Mitsubishi Galant Fortis, Mitsubishi RVR, Mitsubishi Lancer 1.8 CY0 2007, Nissan Murano, Nissan Teana, Nissan Maxima, Nissan Presage, Nissan X-Trail, Nissan Lafesta, Nissan Serena, Nissan Bluebird Sylphy, Nissan Dualis, Suzuki Kizachi, Suzuki SX4, Dodge Caliber, Jeep Compass, Jeep Patriot and other models with CVT-transmission JATCO JF011E (RE0F10A, F1CJA) or JF010E (RE0F09A).

Maintenance-filling under normal operating conditions.

Quality Classification:

RAVENOL CVTF NS2/J1 Fluid is tried and tested for aggregates specifying:

Recommendations: Nissan CVT NS-2 KLE52-0002, KLE52-0004, Mitsubishi S0001401,

PSA Standard 9735EF, Suzuki CVT Fluid Green-1 99000-22B15-046

Technical Characteristics:

RAVENOL CVTF NS2/J1 Fluid offers:

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- A high thermal and oxidative stability
- An excellent cooling capacity

Technical Values:

Characteristics	unit	data	test according to
Colour		green	visual
Density at 20 °C	kg/m ³	847	EN ISO 12185
Pour point	°C	- 42	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data.

Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle.

Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission.

Ravensberger Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems occur please consult a technician.