

Ravensberger Schmierstoffvertrieb GmbH
Postfach 1163
33819 Werther
Tel.: 05203/9719-0
Fax.: 05203/9719-40 / 41

- Certificate / ProductInformation-

RAVENOL CVT Fluid

Art. 1211110

ATF Professional Line

Description:

RAVENOL CVT Fluid is a fully synthetic ATF for the latest generation of CVT transmission.

RAVENOL CVT Fluid guarantees an optimum of power transmission.

RAVENOL CVT Fluid is based on fully synthetic oil (PAO) with a special additive and inhibition to ensure the proper operation of the automatic transmission.

Application:

RAVENOL CVT Fluid was developed for use in CVT transmission (Steel Belt Continuously Variable Transmission).

RAVENOL CVT Fluid ensures a stable viscosity under high mechanical stress in the transmission elements (push belt).

Quality classification:

RAVENOL CVT Fluid is tried and tested for aggregates specifying:

BMW CVT EZL 799A

Ford EU WSS-M2C928-A, Focus C-Max CFT23

Ford USA WSS-M2C933-A, XT-7-QCFT Freestyle, Five Hundred CFT30

Honda CVT Fluid 08200-9006, HMMF Ultra Fluid 08260-99904, 08260-99907

MB 236.20 A 0019894603

Mazda TFF CVT Fluid TC JWS3320 K020-W0-051W

Nissan CVT Fluid NS-1, KLE50 00002, KLE50 00004

Opel/GM 1940713

Subaru i-CVT Fluid K0415-YA090

Suzuki S-CVT 99000-22801-000

Toyota CVT Fluid TC 08886-02105

VW/AUDI G052180A1/A2/A6, TL 52180, VW G 052 516 A2

Mini Cooper CVT

Technical characteristics:

RAVENOL CVT Fluid offers:

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very low pour point
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- Neutral behaviour towards sealing materials
- Neutral behaviour by inhibition to non-ferrous metals

Technical values:

Characteristics	unit	data	test according to
Colour		brown	
Density at 20 °C	kg/m ³	847	EN ISO 12185
Pour point	°C	- 50	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data.

Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle.

Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission.

Ravensberger Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems occur please consult a technician.

22.03.13