

RAVENOL Getriebeoel LS SAE 75W-90

Art. 1222102

Description:

RAVENOL Getriebeoel LS SAE 75W-90 is a semi-synthetic lubricant for mechanical transmissions.

RAVENOL Getriebeoel LS SAE 75W-90 is designed based on high-quality solvent refined and synthetic base oils with special additive treatment and inhibition for higher stress on manual transmission oils and ensuring trouble-free transmission function.

Application Directions:

RAVENOL Getriebeoel LS SAE 75W-90 was developed specifically for use in differential gear units with limited slip. It also ensures trouble-free lubrication in self-locking, hypoid geared transmissions.

Quality Classification:

RAVENOL Getriebeoel LS SAE 75W-90 is tried and tested for aggregates specifying:

Specifications: API GL-5, MIL-L-2105D

Recommendations: ZF TE-ML 05C/D

Technical Characteristics:

RAVENOL Getriebeoel LS SAE 75W-90 offers:

- excellent oxidation stability
- excellent protection against rust and corrosion
- prevents foaming
- outstanding extreme pressure properties
- excellent limited slip properties
- fuel savings

Technical Values:

Characteristics		unit	data	test according to
Colour			yellow	visual
Density	at 20 °C	kg/m ³	863	EN ISO 12185
Viscosity	at 40 °C	mm ² /s	81,5	DIN 51 562
	at 100 °C	mm ² /s	14,5	DIN 51 562
Viscosity index VI			188	DIN ISO 2909
Flash point (COC)		°C	202	DIN ISO 2592
Pour point		°C	-42	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.