

- Certificate / Product Information -

**RAVENOL Getriebeoel EPX SAE 85W-140 GL 5**

Art. 1223211

**Description:**

**RAVENOL Getriebeoel EPX SAE 85W-140 GL 5** is a lubricating oil for mechanical gears based on high quality and solvent refined base oils. Special extreme pressure (EP)-active substances and selected additives give excellent lubricating oil properties.

**RAVENOL Getriebeoel EPX SAE 85W-140 GL 5** is designed for use with maximum duty, hypoid gearing gears (axel drive, manual transmission, etc.), so far extreme pressure gear oils are required.

**Application Directions:** **RAVENOL Getriebeoel EPX SAE 85W-140 GL 5** is used with maximum duty, hypoid gearing gears (axel drive, manual transmission, etc.).

**Quality Classification:**

**RAVENOL Getriebeoel EPX SAE 85W-140 GL 5** is tried and tested for aggregates specifying:

Specifications: API GL-5, MIL-L-2105 D

Recommendations: ZF TE-ML 05A, 16D, 21A, Ford M2C-9002A, MAN 342 Type M-1, CS 3000B, Mack GO-G, GM

**Technical Characteristics:**

**RAVENOL Getriebeoel EPX SAE 85W-140 GL 5** offers:

- a very good oxidation stability
- widest possible protection against rust and corrosion
- no foam formation
- excellent extreme pressure properties
- low pour point
- neutral behaviour towards metals and sealing materials

**Technical Values:**

Characteristics		unit	data	test according to
<b>Colour</b>			brown	visually
<b>Density</b>	at 20°C	kg/m <sup>3</sup>	899	EN ISO 12185
<b>Viscosity</b>	at 40°C	mm <sup>2</sup> /s	355,0	DIN 51 562
	at 100°C	mm <sup>2</sup> /s	26,4	DIN 51 562
<b>Viscosity index VI</b>			99	DIN ISO 2909
<b>Flash point (COC)</b>		°C	224	DIN ISO 2592
<b>Pour point</b>		°C	- 24	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.